

PRODUCT ADVICE

EXTERIOR MASONRY PAINT



- Availability:** In 5 litre tins only. In Farrow & Ball colours excluding: 30, 42, 43, 50, 51, 53, 56, 66, 70, 74, 93, 94, 95, 96, 212, 217, 220, 222, 223, 224 and 248, 253, 254, 255 and 256. Available direct from the factory, Farrow & Ball Showrooms and selected stockists nationwide.
- Formulation:** A highly durable and resistant water based paint containing a wide spectrum film biocide to protect surfaces against algal and fungal attack. Matt in finish.
- Usage:** To protect all exterior surfaces constructed of masonry, cement, stone, brick, block work, roughcast and chip. Offers a smooth, matt, solvent free, high durable finish that protects against extreme weather conditions, water penetration, bacterial contamination and resists dirt pick up. It also has the ability to fill cracks and withstand structural movements.
- Sheen Level:** 2%
- Surface Preparation:** Ensure all surfaces are sound, clean, dry and free from dirt, grease and other contamination. Surfaces that are unsound may not successfully accept further paint layers; if in doubt seek professional advice.
- Fungal or algal contaminated surfaces** - should be decontaminated with an appropriate treatment or by a solution of diluted bleach and allowed to dry completely. Scrape back unsound surfaces and brush clean before applying Farrow & Ball Stabilising Primer.
- New cement rendered surfaces** - after weathering for up to 6 months apply Farrow & Ball Stabilising Primer.
- Serious structural damaged surfaces** - such as cracking or loose cement must be repaired before paint is applied. Patch prime any repaired or seriously degraded areas with 2 coats of Farrow & Ball Stabilising Primer.
- Unsound surfaces** - alkaline, powdery or porous surfaces should be primed using Farrow & Ball Stabilising Primer; one or two coats should be applied by brush, working well into the surface. Allow to fully dry.
- Lime render surface** - as this is designed to allow vapour transmission, obtain structural advice before selecting a coating system. Exterior Masonry may not be suitable
- Painting:** Stir thoroughly before use. Once the appropriate surface preparation is completed apply two coats of Exterior Masonry Paint by brush taking care not to apply too thickly in hollows and angled sections. Do not apply in temperatures less than 5° or if there is a likelihood of rain. Best applied early in the day to allow drying before evening condensation. When more than one tin of the same colour is to be used ensure that batch numbers are identical or intermix before use.
- Washability:** Completely washable and wipeable.
- Coverage:** Up to 40 square metres per 5 litres, depending on the surface being painted.
- Drying Time:** Touch dry in one hour, hard dry in three hours and re-coat from five hours.
- Thinners:** Water only if required.
- Storage:** This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

PRODUCT ADVICE

EXTERIOR MASONRY PAINT



Disposal:	Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact your local Environment Agency office.
Health & Safety:	Ensure good ventilation during application and drying. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.
Environment	2010 max. permitted limit grammes per litre 40 g/l
	CATEGORY c
	VOC content g/l: 1.71 g/l
	VOC content w/w: 0.135 %
	Classification: Minimal

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

Issue 5 January 2009