

PRODUCT ADVICE

DEAD FLAT & EGGSHELL VARNISH



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml and 2.5 litre tins. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: Ideal for interior bare wood and painted wood or metal surfaces. Suitable for use over water based and oil based products. **Please note the lower the sheen level the lower the level of protection, using the Farrow & Ball Eggshell Varnish will provide more protection than the Farrow & Ball Dead Flat Varnish.**

Preparation: All surfaces must be sound, clean, dry and free from dirt, grease and other contamination. **Flaking or peeling may occur if painting over weak paint layers.**

Considerations This product is white, but will dry clear.

Painting: **Do not paint in temperatures below 10°C or excessive heat above 30°C. Do not apply in damp conditions.** Stir thoroughly before use - this is most important especially with the Dead Flat Varnish.

Interior bare wood and painted surfaces: **Following above preparation, apply by brush, roller or spray. If applying more than one coat, surface may be lightly rubbed down using fine sandpaper in between coats.**

Clean up: Clean brushes and rollers with warm soapy water.

Formulation: A water based paint made using a traditional alkyd resin.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. **Safety Data Sheets are available for professional users on request.**

Environment: **Actual VOC content g/l** 25 g/l (both Varnishes)

VOC content w/w: 1.90% (both Varnishes)

Classification: Low (both Varnishes)

2010 max. permitted limit grams per litre 130 g/l

CATEGORY e

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK

PRODUCT ADVICE

DEAD FLAT & EGGSHELL VARNISH



Coverage	Drying Time	Recoat Time	Sheen Level
Up to 12 m ² per litre.	Touch dry 1 hour	Re-coat 4 hours (depending on conditions and film thickness)	Dead Flat Varnish 2% Eggshell Varnish 20%

Issue 3 January 2012

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK