

PRODUCT ADVICE

WOOD KNOT & RESIN BLOCKING PRIMER



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml and 2.5 litre tins. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: For interior and exterior wood. For use on knotty areas, resinous softwoods such as Columbian pine and oily hardwoods. Helps to prevent stains appearing on the surface.

Preparation: All surfaces must be sound, clean, dry and free from dirt, grease and other contamination. Ensure any resinous residue is removed.

The temperature of the room being painted must stay above 10 °C whilst the Wood Knot & Resin Blocking Primer is applied and dries.

The humidity of the room must remain low during application and drying. If the wood is damp, allow to dry for at least 48 hours before painting. Moisture content should be below 10%.

Painting: **Do not paint in temperatures below 10°C or excessive heat above 30°C.**

Stir thoroughly before use. Apply by brush or roller.

Knotty areas - patch prime. 2 coats may be required.

Resinous softwoods and oily hardwoods - apply two full coats.

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: N/A

Formulation: Based on a 100% acrylic resin.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the environment office at your local council.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.
Safety Data Sheets are available for professional users on request.

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK

PRODUCT ADVICE

WOOD KNOT & RESIN BLOCKING PRIMER



| | | |
|---------------------|--|--------|
| Environment: | Actual VOC content g/l | 2.7g/l |
| | VOC content w/w: | 0.20% |
| | Classification: | Low |
| | 2010 max. permitted limit grams per litre | 30 g/l |
| | CATEGORY | g |

| Coverage | Drying Time | Recoat Time | Sheen Level |
|---|------------------------|--|-------------|
| Up to 32 m ² per 2.5 litres. | 1-2 hours surface dry. | Minimum 4 hours depending on conditions. | N/A |

Issue 3 January 2012

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK