

PRODUCT ADVICE

DEAD FLAT



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml and US Gallon tins in all Farrow & Ball colours. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: Water based with a dead flat finish. Suitable for use on interior woodwork, plaster and metal surfaces where an exceptional matt, elegant finish is required. Not suitable for use in kitchens, bathrooms, on furniture or areas of heavy wear.

Preparation: All surfaces must be sound, clean, dry and free from dirt, grease and other contamination. **Flaking or peeling may occur if painting over weak paint layers.**

Fill any cracks, holes and open joints with an appropriate flexible filler. Surface filling will require more maintenance. Neutralise when caustic strippers have been used.

Interior bare wood surfaces – where required use Farrow & Ball Wood Knot & Resin Blocking Primer to patch prime knotty or resinous woods. Apply a diluted first coat of Farrow & Ball Interior Wood Primer & Undercoat (20% water) followed by one full coat. Proceed with two coats of Farrow & Ball Dead Flat.

Previously painted interior wood surfaces – sand back areas of paint that have peeled or blistered, to achieve a good 'key'. Apply one full coat of Farrow & Ball Interior Wood Primer & Undercoat. Proceed with two coats of Farrow & Ball Dead Flat.

Interior ferrous metal surfaces – new and previously painted metal surfaces should be thoroughly degreased. Remove any weak paint and rust back to bare metal. Apply two coats of Farrow & Ball Metal Primer & Undercoat. Proceed with two coats of Farrow & Ball Dead Flat.

Interior galvanised surfaces – treat with Etch Primer or Mordant Solution taking care to follow manufacturer's instructions and health and safety advice and clean with a detergent wash when dry. Proceed with two coats of Farrow & Ball Dead Flat.

Unsound surfaces – may not successfully accept further paint layers; if in doubt seek professional advice.

This can be applied to plaster, but we would recommend Farrow & Ball Estate[®] Emulsion as a more appropriate finish.

Painting: Do not paint in temperatures below 50°F or excessive heat above 86°F.

Please check for colour accuracy prior to use as we will not be liable for decorating costs caused as a result of an incorrect colour being applied. When more than one tin of the same colour is to be used ensure that batch numbers are identical or intermix before use.

Load brush well and apply two coats. May be applied by a gloss roller for larger flat areas.

Disclaimer: The information given in these specification sheets and technical advice – whether verbal, in writing or by way of trials – is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_USA

PRODUCT ADVICE

DEAD FLAT



- Painting cont/...** For a perfect finish, lightly sand between coats.
- Airless Spraying** – Good results can be achieved by the set up of either 15 thou 65° or 18 thou 65° angle tip using a pressure of between 2700 psi – see separate spraying sheet for more details.
- Cleaning:** Wipeable – However, this finish does mark easily.
- Formulation:** A water based paint made using a traditional alkyd resin.
- Storage:** This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.
- Disposal:** Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the relevant regulations. For further information contact your local EPA office.
- Health & Safety:** Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.

Farrow & Ball has engaged in a testing program to document conformity with all applicable regulations, bans, standards and other requirements administered by the Consumer Product Safety Commission (CPSC). Information on our conformity assessment efforts, along with all General Conformity Certificates is available at www.farrow-ball.com/compliance.

Safety Data Sheets are available for professional users on request.

- Environment:** Environmentally friendly, VOC (Volatile Organic Compounds) content “ZERO” when tested to US Environmental Protection Agency standards.

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 480ft ² per US Gallon and 95ft ² per 750ml depending on the surface being painted.	1-2 hours. Dark colours may take longer to dry. Hard overnight.	Recoat 4 hours depending on conditions.	2%

Issue 3 – January 2012

Disclaimer: The information given in these specification sheets and technical advice – whether verbal, in writing or by way of trials – is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_USA