PRODUCT ADVICE

METAL PRIMER & UNDERCOAT

All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml tins four colours (15, 26, 49 & White). Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: A primer designed to prevent rust. For both internal and external application.

Preparation: Surfaces must be clean and free from oil, grease, dirt, rust and flaking paint.

New and previously painted metal surfaces should be thoroughly degreased. Remove any weak paint and rust back to bare metal.

Painting: **Do not paint in temperatures below 50°F or excessive heat above 86°F.**
Stir thoroughly before use. Apply two coats by brush.

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: N/A

Formulation: Based on a copolymer emulsion.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with relevant regulations. For further information contact your local EPA office.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Keep out of reach of children.

Farrow & Ball has engaged in a testing program to document conformity with all applicable regulations, bans, standards and other requirements administered by the Consumer Product Safety Commission (CPSC). Information on our conformity assessment efforts, along with all General Conformity Certificates is available at www.farrow-ball.com/compliance.

Safety Data Sheets are available for professional users on request.

Environment: Environmentally friendly, VOC (Volatile Organic Compounds) content "ZERO" when tested to US Environmental Protection Agency standards.

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 95ft² per 750ml	1-2 hours surface dry.	4 hours depending on conditions	N/A

Issue 4 January 2012

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_USA