

PRODUCT ADVICE

MODERN EMULSION



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In US gallon tins in all Farrow & Ball colours. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: For walls that require greater cleaning, Farrow & Ball Modern Emulsion is the ultimate high performance alternative to Farrow & Ball Estate[®] Emulsion.

With slightly more sheen, this finish is ideal for kitchens, bathrooms, hallways, children's rooms and other areas of high usage. For use on internal plaster, lined walls and ceilings.

Preparation: Ensure surfaces are sound, clean, dry and free from dirt, grease and other contamination. **Flaking or peeling may occur if painting over weak paint layers.**

For all surfaces - apply Farrow & Ball Wall & Ceiling Primer & Undercoat to promote adhesion and full colour depth. For further information please refer to the Farrow & Ball Wall & Ceiling Primer & Undercoat Product Advice Sheet.

Painting: Do not paint in temperatures below 50°F or excessive heat above 86°F

Please check for colour accuracy prior to use as we will not be liable for decorating costs caused as a result of an incorrect colour being applied. When more than one tin of the same colour is to be used ensure that batch numbers are identical or intermix before use.

Stir thoroughly before use.

Once the above surface preparation is completed, apply two coats using a brush or roller. If using a roller, always lay off in one direction with a brush.

Useful application hints - care should be taken when using deep shaded colours. Losing the wet edge of the paint during application can lead to a common decorating problem known as "Flashing" (halo effect where two edges of paint meet).

Airless Spraying - Good results can be achieved by the set up of 18 thou 65° angle tip using a pressure of between 2000 - 2700 psi - see separate spraying sheet for more details.

Allow to harden in favourable conditions for 24 hours before normal use of area and it will take a further 2 weeks to achieve maximum toughness.

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: Washable, wipeable and stain resistant.

Formulation: Based on a 100% acrylic resin.

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_USA

PRODUCT ADVICE

MODERN EMULSION



Storage: This product is water based and must be protected from frost and extreme temperature. Use within 6 months of purchase. We accept no responsibility for the deterioration of the contents and packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with relevant regulations. For further information contact your local EPA office.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.

Farrow & Ball has engaged in a testing program to document conformity with all applicable regulations, bans, standards and other requirements administered by the Consumer Product Safety Commission (CPSC). Information on our conformity assessment efforts, along with all General Conformity Certificates is available at www.farrow-ball.com/compliance.

Safety Data Sheets are available for professional users on request.

Environment: Environmentally friendly, VOC (Volatile Organic Compounds) content "ZERO" when tested to US Environmental Protection Agency standards.

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 480ft ² per US gallon	1-2 hours surface dry. Hard overnight	Re-coat a minimum of 4 hours ensuring the surface is completely dry.	7%

Issue 9 January 2012

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_USA